



MICROBE-LIFT® Chemical Water Treatments



AQUA XTREME

- A full function , buffered water conditioner
- Detoxifies nitrite, copper and heavy metals, removes and detoxifies chlorine and ammonia, destroys chloramines, boosts alkalinity
- Adds electrolytes and a slime-coat replacer to reduce stress
- For use in ponds where chloramines are added to the water supply

SIZE	ITEM #	TREATS	APPLICATION RATE
16 OZ.	XTP16	960 GALS.	Shake well before using. Add one teaspoon (5 mL) of MICROBE-LIFT/ Aqua Xtreme per 10 gallons of water: to fully condition tap water in new ponds; before, after or during water additions; or before adding new fish, amphibians, invertebrates or plants. For larger applications, add 1 fl. oz. per 60 gallons of water.
32 OZ.	XTP32	1,920 GALS.	
GALLON	XTPG1	7,680 GALS.	

THE ULTIMATE POND PHOSPHATE REMOVER

MICROBE-LIFT/Pond Phosphate Remover is a polymeric blend with outstanding qualities, including the ability to tie-up large quantities of phosphate without negatively influencing the pond water in any way. Phosphate - caused by the decomposition of organic substances such as food surpluses, dead plant matter and excretion - is only harmless in concentrations below 0.1 ppm in fresh water.

- Safely removes phosphate from pond water
- Will not harm fish or plants

SIZE	ITEM #	TREATS	APPLICATION RATE
16 OZ.	PHOSRE16	UP TO 1,600 GALS.	Use one ounce (5 capfuls) of MICROBE-LIFT/Phosphate Remover per 100 gallons. Depending on water quality, organics and fish waste content, 1 ounce can remove between 1.0 - 1.5 ppm phosphate. If phosphate level is still high, repeat dose. In case of a very high phosphate level, several treatments may be required to eradicate the excess phosphate problem. Always add MICROBE-LIFT/Phosphate Remover to or near the recirculating pump.
32 OZ.	PHOSRE32	UP TO 3,200 GALS.	
GALLON	PHOSREGAL	UP TO 12,800 GALS.	



FLOCCULANT PLUS

A proprietary formulation used to coagulate suspended solids in the pond water. After use, particles in the water settle to the bottom of the pond and/or filter out through the filter system.

- Clears cloudy water
- Safe for aquatic life and plants
- Attracts and precipitates suspended particles
- Improves filtration

SIZE	ITEM #	TREATS	APPLICATION RATE
16 OZ.	FPLUS16	UP TO 2,400 GALS.	Add one ounce (5 capfuls) per 150 gallons of CLOUDY pond water. Maintain aeration and filtration for maximum clarification. After the milky haze period, conditions should clear within 12-24 hours. Dosage may be repeated as necessary.
32 OZ.	FPLUS32	UP TO 4,800 GALS.	
GALLON	FPLUSGAL	UP TO 19,000 GALS.	
16 OZ.	FPLUS16F	UP TO 2,400 GALS.	BILINGUAL FRENCH & ENGLISH PACKAGING